Table of Contents

VasExperts-Acct-Terminate-Cause Attributes and Their Values	3
---	---

VasExperts-Acct-Terminate-Cause Attributes and Their Values

Session termination reasons. All IDs must be sequential, starting from 0 — used in PCRF as an array index for transcoding.

- acct_stop_reason_unspecified (0) reason not explicitly specified.
- acct_stop_reason_user_request (1) explicit session termination by subscriber request or when creating a new session.
- acct stop reason idle timeout (2) session termination due to inactivity timeout.
- acct_stop_reason_session_expired (3) session termination due to allocated session time expiration.
- acct_stop_reason_admin_reset (4) termination by admin request (CoA Disconnect-Request).
- acct_stop_reason_lost_service (5) closure due to DHCP-NAK or service 9 deactivation.
- acct_stop_reason_NAS_error (6) errors detected in the request.
- acct_stop_reason_double_secondary_key (7) session termination with the same unique secondary key.
- acct_stop_reason_coa_reauth (8) reauthorization using CoA.
- acct stop reason callback (9) Stop current session due to reauthorization.
- acct_stop_reason_no_auth_response (10) no response to authorization request.
- acct stop reason NAS switch (11) switching to another SSG.
- acct stop reason CoA Disconnect (12) termination via CoA disconnect.
- acct_stop_reason_source_reboot (13) fastDPI restart detected by counter value decrease [fastPCRF].
- acct stop reason change session id (14) sessionId change [fastPCRF].
- acct_stop_reason_transfer_session_id (15) transferring sessionId to another IP [fastPCRF].
- acct_stop_reason_fastdpi_acct_on (16) FastDPI sent Acct-On/Acct-Off [fastPCRF].
- acct_stop_reason_suspended (17) session moved to "suspended" state due to lost connection with RADIUS server [fastPCRF].
- acct_stop_reason_ppp_changed_IPv6_prefix (18) ppp Pool DHCPv6 Renew returned a different prefix.
- acct_stop_reason_ppp_missing_IPv6_prefix (19) ppp Pool DHCPv6 Renew did not return a prefix.