Table of Contents

Hardware Requirements, Installation, and Update	3
Minimum Hardware Requirements	3
Installation and Update	3
Installation on a Separate Server or VM	3

Hardware Requirements, Installation, and Update

Minimum Hardware Requirements

FastRADIUS can be installed on a SCAT server or on a dedicated server or VM.

- 1. CPU 2 cores
- 2. RAM from 1 GB
- 3. SSD 50 GB
- 4. Operating System VEOS
- 5. Network Interface Card (NIC) 2 ports, for SSH management (+ optional IPFIX sending) and for receiving RADIUS traffic

Installation and Update

The component is included in the standard SSG software package. If used on the same server as SSG, no additional installation is required.

Further updates are performed in the standard way:

yum update fastradius

Installation on a Separate Server or VM

1. Configure precise time synchronization via the ntpd service. NTPD configuration file: /etc/sysconfig/ntpd. To do this, install the precise time service

```
yum install chrony -y
systemctl restart chronyd
timedatectl
```

When running the timedatectl command, the System clock synchronized parameter must have the value yes

2. Connect the vasexperts repository

```
rpm --import http://vasexperts.ru/centos/RPM-GPG-KEY-vasexperts.ru
rpm -Uvh
http://vasexperts.ru/centos/6/x86_64/vasexperts-repo-2-1.noarch.rpm
```

3. Install FastRADIUS

```
yum install fastradius
```

4. Start the service

systemctl start fastradius

5. Enable service autostart at boot

systemctl enable fastradius

6. Check the status (should be running)

systemctl status fastradius